

UNI-PRINTER MODEL UP 400-T

STANDARD FEATURES AND SPECIFICATIONS

Vertical pad motion eliminates pad vibration and resultant delays
Greater work-space area
Rigid frame ensures smooth operation
Modular design enables in-line use
All controls are conveniently located for fast set-up
Programmable
controller Single
auto-mixing cycle
Variable speed
Cycle and pad delay Double print control X-Y-R
pad adjustment Pad stroke adjustment in pick-up
and printing positions
X-Y in Inkwell and plate adjustment
Self-adjusting doctor blade Quick-
change doctor blade and flood bar
Quick-change inkwell and plate
Digital counter
Emergency stop
Transparent side guards
Cycle Capacity - up to 1400 cycles/hour
Drive - electro-pneumatic
Air Supply - 80 psi
Air Consumption -7 cu. ft. /min.
Input Voltage - 115 volts - 50/60 Hz
Weight - 300 lbs.

INKWELL OPTIONS

Inkwell 4" x 6"
Inkwell 4" x 8"
Inkwell 4" x 10"
Doctor Blade Assembly 5"
Doctor Blade Assembly 7"
Doctor Blade Assembly 9"

MACHINE OPTIONS

Steel Floor Stand
Foot Switch
X-Y Table 6" x 8"
X-Y Table 9" x 12"
Rotary Table - Electric Drive

PAINT

Chemical Resistant
Special Colors, add