

UNI-PRINTER MODEL UP 500-P

STANDARD FEATURES AND SPECIFICATIONS

Vertical pad motion eliminates pad vibration and resultant delays
Greater work-space area
Rigid frame ensures smooth operation
Modular design enables in-line use
All controls are conveniently located for fast set-up
Programmable
controller Single
auto-mixing cycle
Variable speed
Cycle and pad
delay Double
print control X-
Y-R pad
adjustment
Pad stroke adjustment in pick-up and printing positions
X-Y Inkwell and plate adjustment
Self-adjusting doctor blade Quick-
change doctor blade and flood bar
Quick-change inkwell and plate
Digital counter
Emergency stop
Transparent side guards
Cycle Capacity - up to 1200 cycles/hour
Drive electro-pneumatic
Air Supply -80 psi
Air Consumption - 8 cult./min.
Input Voltage - 115 volts-50/60 Hz
Weight - 630 lbs.

INKWELL OPTIONS

Inkwell 5" x 8"
Inkwell 5" x 10"
Inkwell 5• x 12"
Doctor Blade Assembly 7"
Doctor Blade Assembly 9"
Doctor Blade Assembly 11"

MACHINE OPTIONS

Foot Switch
X-Y Table 6" x 8"
X-Y Table 9" x 12"
Rotary Table - Electric Drive

PAINT

Chemical Resistant
Special Colors, Add