

UNI-PRINTER MODEL UP 500-T

STANDARD FEATURES AND SPECIFICATIONS

Vertical pad motion eliminates pad vibration and resultant delays
Greater work-space area
Rigid frame ensures smooth operation
Modular design enables in-line use
All controls are conveniently located for fast set-up
Programmable
controller Single
auto-mixing cycle
Variable speed
Cycle and pad delay Double print control X-Y-R
pad adjustment Pad stroke adjustment in pick-up
and printing positions
X-Y Inkwell and plate adjustment
Self-adjusting doctor blade Quick-
change doctor blade and flood bar
Quick-change inkwell and plate
Digital counter
Emergency stop
Transparent side guards
Cycle Capacity - up to 1200 cycles/hour
Drive - electro-pneumatic
Air Supply - 80 psi
Air Consumption - 8 cu.ft./min.
Input Voltage - 115 volts-50/60 Hz
Weight - 350 lbs.

INKWELL OPTIONS

Inkwell 5" x 8"
Inkwell 5" x 10"
Inkwell 5" x 12"
Doctor Blade Assembly 7"
Doctor Blade Assembly 9"
Doctor Blade Assembly 11"

MACHINE OPTIONS

Steel Floor Stand Price
Foot Switch
X-Y Table 6" x 8"
X-Y Table 9" X 12"
Rotary Table - Electric Drive

PAINT

Chemical Resistant
Special Colors, Add